

Abrasive Products

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Date of Issue: 10/18/2022

Version: 1.0

SECTION 1: IDENTIFICATION

1.1. Product Identifier

Product Form: Mixture

Product Name: Abrasive Products

Synonyms: AO, MX, MXD, Regular

1.2. Intended Use of the Product

Polishing various substrates i.e.: metals, wood, polycarbonates

1.3. Name, Address, and Telephone of the Responsible Party

Company

Micro-Surface Finishing Products, Inc.

1217 W 3rd St

PO Box 70

Wilton IA 52778

563.732.3240

www.micro-surface.com

1.4. Emergency Telephone Number

Emergency Number : 563.732.3240

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the Substance or Mixture

GHS-US/CA Classification

Not classified

2.2. Label Elements

GHS-US/CA Labeling

No labeling applicable according to 29 CFR 1910.1200 and the Hazardous Products Regulations (HPR) SOR/2015-17.

Supplemental Information : This product is defined as an "article" under 29CFR 1910.1200 (c), and is therefore exempt from classification and labeling regulation under the US OSHA Hazard Communication Standard and the Canadian Hazardous Product Regulations. This product is physiologically inert in its, current, massive form. However, user-generated dust and/or fumes may pose a physiological hazard if inhaled or ingested. The data presented in the SDS and product instructions is intended to guide the user in the safe handling and use of the product. See the product instructions for proper usage instructions and precautions. Read the product instructions for use before handling.

2.3. Other Hazards

Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

2.4. Unknown Acute Toxicity (GHS-US/CA)

No additional information available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substance

Not applicable

3.2. Mixture

Name	Synonyms	Product Identifier	% *	GHS Ingredient Classification
Adhesive	None Disclosed	(CAS-No.) None Disclosed	30-60	Not classified
Aluminum oxide (Al ₂ O ₃)	Aluminum oxide / .alpha.-Alumina / Alumina / Aluminium oxide / Aluminium oxide (Al ₂ O ₃) / .alpha.-Aluminum oxide / Dialuminum trioxide / Dialuminium trioxide / ALUMINA / Alundum	(CAS-No.) 1344-28-1	30-60	Not classified
Diamond	DIAMOND POWDER / diamond	(CAS-No.) 7782-40-3	30-60	Not classified
Silicon carbide	Silicon carbide (SiC) / Silicon carbide, fibrous / Silicon carbide whiskers / Silicon carbide, non-fibrous / SILICON CARBIDE / silicon carbide / Silicon carbide fibres (with diameter <3 µm, length >5 µm and aspect ratio ≥3:1) / Silicon carbide fibres	(CAS-No.) 409-21-2	30-60	Carc. 1, H350 STOT RE 1, H372

Abrasive Products

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Styrene-butadiene copolymer	Benzene, ethenyl-, polymer with 1,3-butadiene / Butadiene-styrene copolymer / 1,3-Butadiene-styrene copolymer / Butadiene-styrene polymer / 1,3-Butadiene-styrene polymer / Butadiene-styrene resin / Butadiene-styrene rubber / Styrene-1,3-butadiene copolymer / STYRENE/BUTADIENE COPOLYMER / Styrene-butadiene polymer / Styrene/butadiene copolymers / Polymer of styrene and 1,3-butadiene / Styrene-butadiene rubber / 1,3 Butadiene/styrene copolymers / Styrene homopolymer and 1,3-butadiene homopolymer, block copolymer / Polymer of buta-1,3-diene/styrene / Polymer mainly composed of styrene/butadiene	(CAS-No.) 9003-55-8	10-30	Comb. Dust
Polyester/ Cotton fabric	None disclosed	(CAS-No.) None disclosed	1-5	Not classified
2-Hydroxy-4-n-octoxybenzophenone	Benzophenone, 2-hydroxy-4-(octyloxy)- / Methanone, [2-hydroxy-4-(octyloxy)phenyl]phenyl- / Octabenzene / Benzophenone-12 / 2-Hydroxy-4-(octyloxy)benzophenone / 2-Hydroxy-4-n-octyloxybenzophenone / BENZOPHENONE-12 / Methanone, [2-hydroxy-4-(octyloxy)phenyl]phenyl- / 2-Hydroxy-4-(octyloxy) benzophenone / octabenzene	(CAS-No.) 1843-05-6	< 1	Not classified
2-Propenoic acid, 2-methyl-, polymer with ethyl 2-propenoate	Ethyl acrylate, polymer with methacrylic acid / Methacrylic acid, polymer with ethyl acrylate / Polymer, ethyl acrylate and methacrylic acid / Ethyl acrylate-methacrylic acid copolymer / Acrylic acid, 2-methyl-, polymer with ethyl 2-propenoate / Methacrylic acid-ethyl acrylate polymer / Methacrylic acid-ethyl acrylate copolymer / Polymer of [2-methyl-2-propenoic acid] and [ethyl 2-propenoate]	(CAS-No.) 25212-88-8	< 1	Acute Tox. 4 (Inhalation:dust, mist), H332

Full text of H-statements: see section 16

* The actual concentration of ingredient(s) is withheld as a trade secret in accordance with the Hazardous Products Regulations (HPR) SOR/2015-17 and 29 CFR 1910.1200. Percentages are listed in weight by weight percentage (w/w%) for liquid and solid ingredients. Gas ingredients are listed in volume by volume percentage (v/v%). Full text of H-statements: see section 16.

SECTION 4: FIRST AID MEASURES

4.1. Description of First-aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

Inhalation: In the event of dust exposure: When symptoms occur: go into open air and ventilate suspected area. Obtain medical attention if breathing difficulty persists.

Skin Contact: Remove contaminated clothing. Wash with plenty of soap and water. Obtain medical attention if irritation develops or persists.

Eye Contact: Rinse cautiously with water for at least 5 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if irritation develops or persists.

Ingestion: Rinse mouth. Do NOT induce vomiting. Obtain medical attention.

4.2. Most Important Symptoms and Effects Both Acute and Delayed

General: Not expected to present a significant hazard under anticipated conditions of normal use.

Inhalation: Sanding and grinding dusts may be harmful if inhaled and irritating to the respiratory system.

Skin Contact: Direct contact may cause irritation by mechanical abrasion.

Eye Contact: Eye contact with dust may cause mechanical irritation.

Ingestion: Ingestion may cause adverse effects.

Chronic Symptoms: None expected under normal conditions of use. Prolonged inhalation of dust or fumes from this product may cause siderosis, a benign lung disease.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Water spray, fog, carbon dioxide (CO₂), alcohol-resistant foam, or dry chemical.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not considered flammable but may burn at high temperatures.

Explosion Hazard: Product is not explosive.

Reactivity: Hazardous reactions will not occur under normal conditions.

Abrasive Products

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Oxides of silicon, chromium and carbon.

5.4. Reference to Other Sections

Refer to Section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Avoid prolonged contact with eyes, skin and clothing. Avoid breathing dust.

6.1.1. For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protective equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

6.1.2. For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit.

Ventilate area.

6.2. Environmental Precautions

Prevent entry to sewers and public waters.

6.3. Methods and Materials for Containment and Cleaning Up

For Containment: Contain solid spills with appropriate barriers and prevent migration and entry into sewers or streams.

Methods for Cleaning Up: Clean up spills immediately and dispose of waste safely. Recover the product by vacuuming, shoveling or sweeping. Use explosion proof vacuum during cleanup, with appropriate filter. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Additional Hazards When Processed: Carbon/graphite dust is electrically conductive and dust accumulations on electrical equipment can cause short circuits resulting in electrical shock, fire or damage to equipment. Graphite dust may create slippery conditions. . Keep dust levels to a minimum and follow applicable regulations.

Precautions for Safe Handling: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Avoid prolonged contact with eyes, skin and clothing. Avoid breathing dust.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations. Avoid creating or spreading dust. Do not dry clean dust covered objects and floors. Use water plus a cleaning agent for cleanup.

Storage Conditions: Keep container closed when not in use. Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials.

Incompatible Materials: Strong acids, strong bases, strong oxidizers.

7.3. Specific End Use(s)

Polishing various substrates i.e.: metals, wood, polycarbonates

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), OSHA (PEL), or Canadian provincial governments.

Aluminum oxide (Al ₂ O ₃) (1344-28-1)		
USA ACGIH	ACGIH OEL TWA	10 mg/m ³
USA OSHA	OSHA PEL (TWA) [1]	15 mg/m ³ (total dust)
		5 mg/m ³ (respirable fraction)

Abrasive Products

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Alberta	OEL TWA	10 mg/m ³
New Brunswick	OEL TWA	10 mg/m ³ (particulate matter containing no Asbestos and <1% Crystalline silica)
Nunavut	OEL STEL	20 mg/m ³
Nunavut	OEL TWA	10 mg/m ³
Northwest Territories	OEL STEL	20 mg/m ³
Northwest Territories	OEL TWA	10 mg/m ³
Québec	VEMP (OEL TWA)	10 mg/m ³ (containing no Asbestos and <1% Crystalline silica-total dust)
Saskatchewan	OEL STEL	20 mg/m ³
Saskatchewan	OEL TWA	10 mg/m ³
Yukon	OEL STEL	20 mg/m ³ (Al ₂ O ₃)
Yukon	OEL TWA	30 mppcf (Al ₂ O ₃) 10 mg/m ³ (Al ₂ O ₃)
Silicon carbide (409-21-2)		
USA ACGIH	ACGIH OEL TWA	10 mg/m ³ (nonfibrous, inhalable particulate matter, particulate matter containing no asbestos and <1% crystalline silica) 3 mg/m ³ (nonfibrous, respirable particulate matter, particulate matter containing no asbestos and <1% crystalline silica) 0.1 fibers/cm ³ (as determined by the membrane filter method at 400-450X magnification (4-mm objective), using phase-contrast illumination.- respirable fibers, including whiskers, length >5 µm, aspect ratio >=3:1)
USA ACGIH	ACGIH chemical category	Suspected Human Carcinogen fibrous, including whiskers
USA OSHA	OSHA PEL (TWA) [1]	15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction)
USA NIOSH	NIOSH REL (TWA)	10 mg/m ³ (total dust) 5 mg/m ³ (respirable dust)
Alberta	OEL TWA	10 mg/m ³ (nonfibrous-total particulate) 3 mg/m ³ (nonfibrous-respirable particulate) 0.1 fibers/cm ³ (fibrous, including whiskers)
British Columbia	OEL TWA	10 mg/m ³ (nonfibrous-inhalable) 3 mg/m ³ (nonfibrous-respirable) 0.1 fibers/cm ³ (fibrous, including whiskers)
Manitoba	OEL TWA	10 mg/m ³ (particulate matter containing no Asbestos and <1% Crystalline silica-nonfibrous, inhalable particulate matter, particulate matter) 3 mg/m ³ (particulate matter containing no Asbestos and <1% Crystalline silica-nonfibrous, respirable particulate matter, particulate matter) 0.1 fibers/cm ³ (respirable fibers, including whiskers, with length >5 µm, aspect ratio >=3:1 as determined by the membrane filter method at 400-450X magnification (4-mm objective), using phase-contrast illumination.- respirable fibers)
New Brunswick	OEL TWA	10 mg/m ³ (particulate matter containing no Asbestos and <1% Crystalline silica)
Newfoundland & Labrador	OEL TWA	10 mg/m ³ (particulate matter containing no Asbestos and <1% Crystalline silica-nonfibrous, inhalable particulate matter, particulate matter) 3 mg/m ³ (particulate matter containing no Asbestos and <1% Crystalline silica-nonfibrous, respirable particulate matter, particulate matter) 0.1 fibers/cm ³ (respirable fibers, including whiskers, with length >5 µm, aspect ratio >=3:1 as determined by the membrane filter method at 400-450X magnification (4-mm objective), using phase-contrast illumination.- respirable fibers)
Nova Scotia	OEL TWA	10 mg/m ³ (particulate matter containing no Asbestos and <1% Crystalline silica-nonfibrous, inhalable particulate matter, particulate matter)

Abrasive Products

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

		3 mg/m ³ (particulate matter containing no Asbestos and <1% Crystalline silica-nonfibrous, respirable particulate matter, particulate matter) 0.1 fibers/cm ³ (respirable fibers, including whiskers, with length >5 µm, aspect ratio ≥3:1 as determined by the membrane filter method at 400-450X magnification (4-mm objective), using phase-contrast illumination.-respirable fibers)
Nunavut	OEL STEL	20 mg/m ³ (non-fibrous-inhalable fraction) 6 mg/m ³ (non-fibrous-respirable fraction)
Nunavut	OEL TWA	10 mg/m ³ (non-fibrous-inhalable fraction) 3 mg/m ³ (non-fibrous-respirable fraction) 0.1 fibers/cm ³ (fibrous, including whiskers-respirable fibres)
Northwest Territories	OEL STEL	20 mg/m ³ (non-fibrous-inhalable fraction) 6 mg/m ³ (non-fibrous-respirable fraction)
Northwest Territories	OEL TWA	10 mg/m ³ (non-fibrous-inhalable fraction) 3 mg/m ³ (non-fibrous-respirable fraction) 0.1 fibers/cm ³ (fibrous, including whiskers-respirable fibres)
Ontario	OEL TWA	10 mg/m ³ (non-fibrous, particulate matter containing no Asbestos and <1% Crystalline silica-inhalable fraction) 3 mg/m ³ (non-fibrous, particulate matter containing no Asbestos and <1% Crystalline silica-respirable fraction) 0.1 fibers/cm ³ (fibrous, including whiskers, fibres >5 µm in length and an aspect ratio ≥3:1 as determined by the membrane filter method at 400-450 times magnification (4-mm objective), using phase-contrast illumination.-respirable fraction)
Prince Edward Island	OEL TWA	10 mg/m ³ (particulate matter containing no Asbestos and <1% Crystalline silica-nonfibrous, inhalable particulate matter, particulate matter) 3 mg/m ³ (particulate matter containing no Asbestos and <1% Crystalline silica-nonfibrous, respirable particulate matter, particulate matter) 0.1 fibers/cm ³ (respirable fibers, including whiskers, with length >5 µm, aspect ratio ≥3:1 as determined by the membrane filter method at 400-450X magnification (4-mm objective), using phase-contrast illumination.-respirable fibers)
Québec	VEMP (OEL TWA)	10 mg/m ³ (non fibrous, containing no Asbestos and <1% Crystalline silica-total dust) 3 mg/m ³ (non fibrous, containing no Asbestos and <1% Crystalline silica-respirable dust)
Saskatchewan	OEL STEL	20 mg/m ³ (nonfibrous, inhalable fraction) 6 mg/m ³ (nonfibrous, respirable fraction)
Saskatchewan	OEL TWA	0.1 fibers/cm ³ (including whiskers-fibrous, respirable fibres) 10 mg/m ³ (nonfibrous, inhalable fraction) 3 mg/m ³ (nonfibrous, respirable fraction)
Yukon	OEL STEL	20 mg/m ³
Yukon	OEL TWA	30 mppcf 10 mg/m ³

8.2. Exposure Controls

Appropriate Engineering Controls: Suitable eye/body wash equipment should be available in the vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed.

Personal Protective Equipment: Gloves. Protective clothing. Protective goggles. Face shield.



Materials for Protective Clothing: Chemically resistant materials and fabrics.

Abrasive Products

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Hand Protection: Wear protective gloves.

Eye and Face Protection: Chemical safety goggles and face shield during use.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

Other Information: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties

Physical State	: Solid
Appearance	: Nitrile rubber / Plastic
Odor	: No odors that outgas from this product contain Hazardous Air Pollutants (HAPs)
Odor Threshold	: No data available
pH	: No data available
Evaporation Rate	: No data available
Melting Point	: No data available
Freezing Point	: No data available
Boiling Point	: No data available
Flash Point	: No data available
Auto-ignition Temperature	: No data available
Decomposition Temperature	: No data available
Flammability	: No data available
Lower Flammable Limit	: No data available
Upper Flammable Limit	: No data available
Vapor Pressure	: No data available
Relative Vapor Density at 20°C	: No data available
Relative Density	: No data available
Specific Gravity	: No data available
Solubility	: Non-soluble in water.
Partition Coefficient: N-Octanol/Water	: No data available
Viscosity	: No data available

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity:

Hazardous reactions will not occur under normal conditions.

10.2. Chemical Stability:

Stable under recommended handling and storage conditions (see section 7).

10.3. Possibility of Hazardous Reactions:

Hazardous polymerization will not occur.

10.4. Conditions to Avoid:

Direct sunlight, extremely high or low temperatures, and incompatible materials.

10.5. Incompatible Materials:

Strong acids, strong bases, strong oxidizers.

10.6. Hazardous Decomposition Products:

Hazardous decomposition products: Oxides of carbon, chromium and silicon on combustion.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on Toxicological Effects - Product

Acute Toxicity (Oral): Not classified

Acute Toxicity (Dermal): Not classified

Acute Toxicity (Inhalation): Not classified

LD50 and LC50 Data:

No additional information available

Skin Corrosion/Irritation: Not classified

Eye Damage/Irritation: Not classified

Abrasive Products

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Respiratory or Skin Sensitization: Not classified

Germ Cell Mutagenicity: Not classified

Carcinogenicity: Not classified

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: Sanding and grinding dusts may be harmful if inhaled and irritating to the respiratory system.

Symptoms/Injuries After Skin Contact: Direct contact may cause irritation by mechanical abrasion.

Symptoms/Injuries After Eye Contact: Eye contact with dust may cause mechanical irritation.

Symptoms/Injuries After Ingestion: Ingestion may cause adverse effects.

Chronic Symptoms: None expected under normal conditions of use, Prolonged inhalation of dust or fumes from this product may cause siderosis, a benign lung disease.

Potential Adverse human health effects and symptoms: Based on available data, the classification criteria are not met.

11.2. Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

Aluminum oxide (Al₂O₃) (1344-28-1)	
LD50 Oral Rat	> 15900 mg/kg
Diamond (7782-40-3)	
LD50 Dermal Rat	> 2000 mg/kg
LC50 Inhalation Rat	> 5.2 mg/l (Exposure time: 241 min)
2-Hydroxy-4-n-octoxybenzophenone (1843-05-6)	
LD50 Oral Rat	> 10000 mg/kg
LD50 Dermal Rabbit	> 10 g/kg
2-Propenoic acid, 2-methyl-, polymer with ethyl 2-propenoate (25212-88-8)	
LC50 Inhalation Rat	1.03 mg/l/4h
ATE US/CA (dust, mist)	1.50 mg/l/4h
Styrene-butadiene copolymer (9003-55-8)	
IARC Group	3
Silicon carbide (409-21-2)	
IARC Group	2A (respirable)
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecology - General: Not classified.

Aluminum oxide (Al₂O₃) (1344-28-1)	
LC50 Fish 1	> 100 mg/l
EC50 - Crustacea [1]	> 100 mg/l
ErC50 algae	> 100 mg/l
NOEC (Acute)	> 50 mg/l
Diamond (7782-40-3)	
LC50 Fish 1	> 100 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
2-Hydroxy-4-n-octoxybenzophenone (1843-05-6)	
LC50 Fish 1	> 100 mg/l (Exposure time: 96 h - Species: Brachydanio rerio)

12.2. Persistence and Degradability

Abrasive Products	
Persistence and Degradability	Not established.

12.3. Bioaccumulative Potential

Abrasive Products	
Bioaccumulative Potential	Not established.

Abrasive Products

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

2-Hydroxy-4-n-octoxybenzophenone (1843-05-6)

BCF Fish 1 89 – 190

Partition coefficient n-octanol/water (Log Pow) > 6

12.4. Mobility in Soil

Abrasive Products

Ecology - Soil No data available.

12.5. Other Adverse Effects

Other Adverse Effects: None known.

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste Treatment Methods: Can be landfilled or incinerated, when in compliance with local regulations.

Sewage Disposal Recommendations: Do not dispose of waste into sewer.

Waste Disposal Recommendations: Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

Additional Information: Incineration is the preferred method for disposal of waste product.

Ecology - Waste Materials: Avoid release to the environment.

SECTION 14: TRANSPORT INFORMATION

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

14.1. In Accordance with DOT

Not regulated for transport

14.2. In Accordance with IMDG

Not regulated for transport

14.3. In Accordance with IATA

Not regulated for transport

14.4. In Accordance with TDG

Not regulated for transport

SECTION 15: REGULATORY INFORMATION

15.1. US Federal Regulations

Styrene-butadiene copolymer (9003-55-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

EPA TSCA Regulatory Flag XU - XU - indicates a substance exempt from reporting under the Chemical Data Reporting Rule, (40 CFR 711).

Aluminum oxide (Al₂O₃) (1344-28-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

Subject to reporting requirements of United States SARA Section 313

SARA Section 313 - Emission Reporting 1 % (fibrous forms)

Diamond (7782-40-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

Silicon carbide (409-21-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

2-Hydroxy-4-n-octoxybenzophenone (1843-05-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

2-Propenoic acid, 2-methyl-, polymer with ethyl 2-propenoate (25212-88-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

EPA TSCA Regulatory Flag XU - XU - indicates a substance exempt from reporting under the Chemical Data Reporting Rule, (40 CFR 711).

Abrasive Products

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

15.2. US State Regulations

Aluminum oxide (Al₂O₃) (1344-28-1)

U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Massachusetts - Right To Know List
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

Silicon carbide (409-21-2)

U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Massachusetts - Right To Know List

15.3. Canadian Regulations

Styrene-butadiene copolymer (9003-55-8)

Listed on the Canadian DSL (Domestic Substances List)

Aluminum oxide (Al₂O₃) (1344-28-1)

Listed on the Canadian DSL (Domestic Substances List)

Diamond (7782-40-3)

Listed on the Canadian DSL (Domestic Substances List)

Silicon carbide (409-21-2)

Listed on the Canadian DSL (Domestic Substances List)

2-Hydroxy-4-n-octoxybenzophenone (1843-05-6)

Listed on the Canadian DSL (Domestic Substances List)

2-Propenoic acid, 2-methyl-, polymer with ethyl 2-propenoate (25212-88-8)

Listed on the Canadian DSL (Domestic Substances List)

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Date of Preparation or Latest : 10/18/2022

Revision

Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200 and Canada's Hazardous Products Regulations (HPR) SOR/2015-17.

GHS Full Text Phrases:

H332	Harmful if inhaled
H350	May cause cancer.
H372	Causes damage to organs through prolonged or repeated exposure

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

NA GHS SDS 2015 (Can, US)

Final Finish

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).
Date of Issue: 11/10/2022 Version: 1.0

SECTION 1: IDENTIFICATION

1.1. Product Identifier

Product Form: Mixture

Product Name: Final Finish

1.2. Intended Use of the Product

Polish to remove residual haze on coatings, paint or plastics.

1.3. Name, Address, and Telephone of the Responsible Party

Company

Micro-Surface Finishing Products, Inc.

1217 W 3rd St

PO Box 70

Wilton IA 52778

563.732.3240

www.micro-surface.com

1.4. Emergency Telephone Number

Emergency Number : 563.732.3240

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the Substance or Mixture

GHS-US/CA Classification

Flammable liquids Category 2	H225
Skin corrosion/irritation Category 2	H315
Serious eye damage/eye irritation Category 2	H319
Specific target organ toxicity (repeated exposure) Category 1	H372
Hazardous to the aquatic environment - Acute Hazard Category 3	H402
Hazardous to the aquatic environment - Chronic Hazard Category 3	H412

2.2. Label Elements

GHS-US/CA Labeling

Hazard Pictograms (GHS-US/CA)

:



GHS02



GHS07



GHS08

Signal Word (GHS-US/CA)

: Danger

Hazard Statements (GHS-US/CA)

: H225 - Highly flammable liquid and vapor.

H315 - Causes skin irritation.

H319 - Causes serious eye irritation.

H372 - Cause damage to organs (central nervous system) through prolonged or repeated exposure (inhalation).

H402 - Harmful to aquatic life.

H412 - Harmful to aquatic life with long lasting effects.

Precautionary Statements (GHS-US/CA) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 - Keep container tightly closed.

P240 - Ground/bond container and receiving equipment.

P241 - Use explosion-proof electrical, ventilating, and lighting equipment.

P242 - Use only non-sparking tools.

P243 - Take action to prevent static discharges.

P260 - Do not breathe vapors, mist, or spray.

P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.

P270 - Do not eat, drink or smoke when using this product.

P273 - Avoid release to the environment.

Final Finish

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

P280 - Wear protective gloves, protective clothing, and eye protection.
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water .
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P314 - Get medical advice/attention if you feel unwell.
P321 - Specific treatment (see section 4 on this SDS).
P332+P313 - If skin irritation occurs: Get medical advice/attention.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P370+P378 - In case of fire: Use appropriate media (see section 5) to extinguish.
P403+P235 - Store in a well-ventilated place. Keep cool.
P501 - Dispose of contents/container in accordance with local, regional, national, and international regulations.

2.3. Other Hazards

Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

2.4. Unknown Acute Toxicity (GHS-US/CA)

No additional information available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substance

Not applicable

3.2. Mixture

Name	Synonyms	Product Identifier	% *	GHS Ingredient Classification
Naphtha, petroleum, hydrotreated light	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics / Naphtha, petroleum, hydrotreated light (A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C4-11 and boiling in the range of approximately minus 20-190°C.) / Naphtha (petroleum), hydrotreated light	(CAS-No.) 64742-49-0	7 - 13	Flam. Liq. 3, H226 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
Solvent naphtha, petroleum, medium aliphatic	Aliphatic naphtha / Medium aliphatic solvent naphtha / White spirit type 0 / Solvent naphtha(petroleum), medium aliphatic / Solvent naphtha, petroleum, medium aliphatic (A complex combination of hydrocarbons obtained from the distillation of crude oil or natural gasoline. It consists predominantly of saturated hydrocarbons having carbon numbers predominantly in the range of C9-12 and boiling in the range of approximately 140-220°C.) / Aliphatic petroleum solvent (naphtha) / Stoddard chloride / Stoddard solvent / Medium aliphatic solvent naphtha (petroleum) / Solvent naphtha (petroleum), medium aliphatic; Straight run kerosine [A complex	(CAS-No.) 64742-88-7	5 - 10	Flam. Liq. 3, H226 Skin Irrit. 2, H315 STOT SE 3, H336 STOT RE 1, H372 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411

Final Finish

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

	combination of hydrocarbons obtained from the distillation of crude oil or natural gasoline. It consists predominantly of saturated hydrocarbons having carbon numbers predominantly in the range of C9 through C12 and boiling in the range of approximately 140°C to 220°C (284°F to 428°F). / Mineral spirits / Solvent naphtha medium aliphatic / Solvent naphtha, medium heavy, aliphatic hydrocarbons / Stoddard Solvent (Type IIC) / Naphtha, solvent (petroleum), medium aliphatic / Solvent naphtha (petroleum), medium aliphatic			
Stearic acid	1-Heptadecanecarboxylic acid / Neo-fat 18 / n-Octadecanoic acid / Octadecanoic acid / STEARIC ACID / stearic acid	(CAS-No.) 57-11-4	1 - 5	Comb. Dust
Poly(oxy-1,2-ethanediyl), .alpha.,.alpha.'-[[[3-(decyloxy)propyl]methyliminio]di-2,1-ethanediyl]bis[.omega.-hydroxy-, branched, chlorides	Poly(oxy-1,2-ethanediyl), .alpha.,.alpha.'-[[[3-(decyloxy)propyl]methylimino]di-2,1-ethanediyl]bis[.omega.-hydroxy-, branched, chlorides / .alpha.,.alpha.'-[[[3-(Decyloxy)propyl]methyliminio]di-2,1-ethanediyl]bis[.omega.-hydroxypoly(oxy-1,2-ethanediyl)], branched, chlorides / Poly(oxy-1,2-ethanediyl), a,a'-[[[3-(decyloxy)propyl]methylimino]di-2,1-ethanediyl]bis[w-hydroxy-, branched, chlorides	(CAS-No.) 68478-94-4	1.8 – 2.3	Skin Corr. 1, H314 Eye Dam. 1, H318
Triethanolamine	Tris(hydroxyethyl)amine / Trolamine / Tri(2-hydroxyethyl)amine / TRIETHANOLAMINE / Tris(2-hydroxyethyl)amine / TEA / 2,2',2''-Nitrilotriethanol / Ethanol, 2,2',2''-nitrilotris- / Ethanol, 2,2',2''-nitrilotri-	(CAS-No.) 102-71-6	0.1 - 1	Not classified
Isopropyl alcohol	2-Propanol / Isopropanol / Propan-2-ol / ISOPROPYL ALCOHOL / Propanol, 2- / 2-Propyl alcohol / 2-Hydroxypropane / Isopropyl alcohol	(CAS-No.) 67-63-0	0.3 – 0.6	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Acrylic acid	Acroleic acid / Propenoic acid / 2-Propenoic acid / Acrylic acid, stabilized / Prop-2-enoic acid / ACRYLIC ACID	(CAS-No.) 79-10-7	0.1 - 1	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Corr. 1A, H314 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Acute 1, H400 Aquatic Chronic 2, H411

Final Finish

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Octamethylcyclotetrasiloxane	Cyclotetrasiloxane, octamethyl- / Cyclotetrasiloxane, 2,2,4,4,6,6,8,8-octamethyl- / D4 / 2,2,4,4,6,6,8,8-Octamethylcyclotetrasiloxane / Cyclomethicone 4	(CAS-No.) 556-67-2	≤ 0.004	Flam. Liq. 3, H226 Repr. 2, H361 Aquatic Chronic 1, H410
------------------------------	--	--------------------	---------	--

Full text of H-statements: see section 16

*Percentages are listed in weight by weight percentage (w/w%) for liquid and solid ingredients. Gas ingredients are listed in volume by volume percentage (v/v%).

** The actual concentration of ingredient(s) is withheld as a trade secret in accordance with the Hazardous Products Regulations (HPR) SOR/2015-17 and 29 CFR 1910.1200.

SECTION 4: FIRST AID MEASURES

4.1. Description of First-aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

Inhalation: When symptoms occur: go into open air and ventilate suspected area. Obtain medical attention if breathing difficulty persists.

Skin Contact: Immediately remove contaminated clothing. Immediately drench affected area with water for at least 15 minutes. Obtain medical attention if irritation develops or persists.

Eye Contact: Immediately rinse with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if irritation develops or persists.

Ingestion: Rinse mouth. Do NOT induce vomiting. Obtain medical attention.

4.2. Most Important Symptoms and Effects Both Acute and Delayed

General: Causes skin irritation. Causes serious eye irritation. Cause damage to organs (central nervous system) through prolonged or repeated exposure (inhalation).

Inhalation: Prolonged exposure may cause irritation.

Skin Contact: Redness, pain, swelling, itching, burning, dryness, and dermatitis.

Eye Contact: Contact causes severe irritation with redness and swelling of the conjunctiva.

Ingestion: Ingestion may cause adverse effects.

Chronic Symptoms: Cause damage to organs (central nervous system) through prolonged or repeated exposure (inhalation).

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Dry chemical powder, alcohol-resistant foam, carbon dioxide (CO₂). Water may be ineffective but water should be used to keep fire-exposed container cool.

Unsuitable Extinguishing Media: Do not use a heavy water stream. A heavy water stream may spread burning liquid.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Highly flammable liquid and vapor.

Explosion Hazard: May form flammable or explosive vapor-air mixture.

Reactivity: Reacts violently with strong oxidizers. Increased risk of fire or explosion.

5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products:

Other Information: Do not allow run-off from fire fighting to enter drains or water courses.

Final Finish

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

5.4. Reference to Other Sections

Refer to Section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Avoid breathing (vapor, mist, spray). Avoid all contact with skin, eyes, or clothing. Do not get in eyes, on skin, or on clothing. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking. Use special care to avoid static electric charges.

6.1.1. For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protective equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel. Stop leak if safe to do so.

6.1.2. For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Eliminate ignition sources first, then ventilate the area.

6.2. Environmental Precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

6.3. Methods and Materials for Containment and Cleaning Up

For Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. As an immediate precautionary measure, isolate spill or leak area in all directions.

Methods for Cleaning Up: Clean up spills immediately and dispose of waste safely. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill. Absorb and/or contain spill with inert material. Do not take up in combustible material such as: saw dust or cellulosic material. Use only non-sparking tools.

6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Additional Hazards When Processed: Handle empty containers with care because residual vapors are flammable.

Precautions for Safe Handling: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Avoid breathing vapors, mist, spray. Avoid contact with skin, eyes and clothing. Take precautionary measures against static discharge. Use only non-sparking tools.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations. Take action to prevent static discharges. Ground and bond container and receiving equipment. Use explosion-proof electrical, ventilating, and lighting equipment.

Storage Conditions: Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Store in a well-ventilated place. Keep container tightly closed. Keep in fireproof place.

Incompatible Materials: Oxidizers. Avoid aluminum at higher temperatures. Halogenated compounds.

7.3. Specific End Use(s)

Polish to remove residual haze on coatings, paint or plastics.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), OSHA (PEL), or Canadian provincial governments.

Acrylic acid (79-10-7)		
USA ACGIH	ACGIH OEL TWA [ppm]	2 ppm
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen, Skin - potential significant contribution to overall exposure by the cutaneous route
USA NIOSH	NIOSH REL (TWA)	6 mg/m ³
USA NIOSH	NIOSH REL TWA [ppm]	2 ppm

Final Finish

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Alberta	OEL TWA	5.9 mg/m ³
Alberta	OEL TWA [ppm]	2 ppm
British Columbia	OEL TWA [ppm]	2 ppm
Manitoba	OEL TWA [ppm]	2 ppm
New Brunswick	OEL TWA	5.9 mg/m ³
New Brunswick	OEL TWA [ppm]	2 ppm
Newfoundland & Labrador	OEL TWA [ppm]	2 ppm
Nova Scotia	OEL TWA [ppm]	2 ppm
Nunavut	OEL STEL [ppm]	4 ppm
Nunavut	OEL TWA [ppm]	2 ppm
Northwest Territories	OEL STEL [ppm]	4 ppm
Northwest Territories	OEL TWA [ppm]	2 ppm
Ontario	OEL TWA [ppm]	2 ppm
Prince Edward Island	OEL TWA [ppm]	2 ppm
Québec	VEMP (OEL TWA)	5.9 mg/m ³
Québec	VEMP (OEL TWA) [ppm]	2 ppm
Saskatchewan	OEL STEL [ppm]	4 ppm
Saskatchewan	OEL TWA [ppm]	2 ppm
Triethanolamine (102-71-6)		
USA ACGIH	ACGIH OEL TWA	5 mg/m ³
Alberta	OEL TWA	5 mg/m ³
British Columbia	OEL TWA	5 mg/m ³
Manitoba	OEL TWA	5 mg/m ³
New Brunswick	OEL TWA	5 mg/m ³
Newfoundland & Labrador	OEL TWA	5 mg/m ³
Nova Scotia	OEL TWA	5 mg/m ³
Nunavut	OEL STEL	10 mg/m ³
Nunavut	OEL TWA	5 mg/m ³
Northwest Territories	OEL STEL	10 mg/m ³
Northwest Territories	OEL TWA	5 mg/m ³
Ontario	OEL TWA	3.1 mg/m ³
Ontario	OEL TWA [ppm]	0.5 ppm
Prince Edward Island	OEL TWA	5 mg/m ³
Québec	VEMP (OEL TWA)	5 mg/m ³
Saskatchewan	OEL STEL	10 mg/m ³
Saskatchewan	OEL TWA	5 mg/m ³
Isopropyl alcohol (67-63-0)		
USA ACGIH	ACGIH OEL TWA [ppm]	200 ppm
USA ACGIH	ACGIH OEL STEL [ppm]	400 ppm
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA ACGIH	BEI (BLV)	40 mg/l Parameter: Acetone - Medium: urine - Sampling time: end of shift at end of workweek (background, nonspecific)
USA OSHA	OSHA PEL (TWA) [1]	980 mg/m ³
USA OSHA	OSHA PEL (TWA) [2]	400 ppm
USA NIOSH	NIOSH REL (TWA)	980 mg/m ³
USA NIOSH	NIOSH REL TWA [ppm]	400 ppm
USA NIOSH	NIOSH REL (STEL)	1225 mg/m ³
USA NIOSH	NIOSH REL STEL [ppm]	500 ppm
USA IDLH	IDLH [ppm]	2000 ppm (10% LEL)
Alberta	OEL STEL	984 mg/m ³

Final Finish

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Alberta	OEL STEL [ppm]	400 ppm
Alberta	OEL TWA	492 mg/m ³
Alberta	OEL TWA [ppm]	200 ppm
British Columbia	OEL STEL [ppm]	400 ppm
British Columbia	OEL TWA [ppm]	200 ppm
Manitoba	OEL STEL [ppm]	400 ppm
Manitoba	OEL TWA [ppm]	200 ppm
New Brunswick	OEL STEL	1230 mg/m ³
New Brunswick	OEL STEL [ppm]	500 ppm
New Brunswick	OEL TWA	983 mg/m ³
New Brunswick	OEL TWA [ppm]	400 ppm
Newfoundland & Labrador	OEL STEL [ppm]	400 ppm
Newfoundland & Labrador	OEL TWA [ppm]	200 ppm
Nova Scotia	OEL STEL [ppm]	400 ppm
Nova Scotia	OEL TWA [ppm]	200 ppm
Nunavut	OEL STEL [ppm]	400 ppm
Nunavut	OEL TWA [ppm]	200 ppm
Northwest Territories	OEL STEL [ppm]	400 ppm
Northwest Territories	OEL TWA [ppm]	200 ppm
Ontario	OEL STEL [ppm]	400 ppm
Ontario	OEL TWA [ppm]	200 ppm
Prince Edward Island	OEL STEL [ppm]	400 ppm
Prince Edward Island	OEL TWA [ppm]	200 ppm
Québec	VECD (OEL STEL)	1230 mg/m ³
Québec	VECD (OEL STEL) [ppm]	500 ppm
Québec	VEMP (OEL TWA)	985 mg/m ³
Québec	VEMP (OEL TWA) [ppm]	400 ppm
Saskatchewan	OEL STEL [ppm]	400 ppm
Saskatchewan	OEL TWA [ppm]	200 ppm
Yukon	OEL STEL	1225 mg/m ³
Yukon	OEL STEL [ppm]	500 ppm
Yukon	OEL TWA	980 mg/m ³
Yukon	OEL TWA [ppm]	400 ppm
Octamethylcyclotetrasiloxane (556-67-2)		
USA AIHA	WEEL TWA [ppm]	10 ppm
Stearic acid (57-11-4)		
USA ACGIH	ACGIH OEL TWA	10 mg/m ³ (inhalable particulate matter (Stearates)) 3 mg/m ³ (respirable particulate matter (Stearates))
British Columbia	OEL TWA	10 mg/m ³ (does not include Stearates of toxic metals-inhalable (Stearates)) 3 mg/m ³ (does not include Stearates of toxic metals-respirable (Stearates))
Manitoba	OEL TWA	10 mg/m ³ (inhalable particulate matter (Stearates)) 3 mg/m ³ (respirable particulate matter (Stearates))
Newfoundland & Labrador	OEL TWA	10 mg/m ³ (inhalable particulate matter (Stearates)) 3 mg/m ³ (respirable particulate matter (Stearates))
Nova Scotia	OEL TWA	10 mg/m ³ (inhalable particulate matter (Stearates)) 3 mg/m ³ (respirable particulate matter (Stearates))
Ontario	OEL TWA	10 mg/m ³ (except stearates of toxic metals-inhalable particulate matter) 3 mg/m ³ (except stearates of toxic metals-respirable particulate matter)

Final Finish

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Prince Edward Island	OEL TWA	10 mg/m ³ (inhalable particulate matter (Stearates)) 3 mg/m ³ (respirable particulate matter (Stearates))
Québec	VEMP (OEL TWA)	10 mg/m ³ (Stearates)

8.2. Exposure Controls

Appropriate Engineering Controls: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed. Gas detectors should be used when flammable gases or vapors may be released. Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof equipment.

Personal Protective Equipment: Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection.



Materials for Protective Clothing: Chemically resistant materials and fabrics. Wear fire/flamm resistant/retardant clothing.

Hand Protection: Wear protective gloves.

Eye and Face Protection: Chemical safety goggles.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

Other Information: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties

Physical State	: Liquid
Appearance	: White Cream
Odor	: According to product specification
Odor Threshold	: No data available
pH	: No data available
Evaporation Rate	: No data available
Melting Point	: No data available
Freezing Point	: No data available
Boiling Point	: 48 – 70 °C (118,4 – 158 °F) (Hydrocarbons, C6, isoalkanes, <5% n-hexane (CAS-No. 64742-49-0))
Flash Point	: < 0 °C (32 °F) (Hydrocarbons, C6, isoalkanes, <5% n-hexane (CAS-No. 64742-49-0))
Auto-ignition Temperature	: > 200 °C (392 °F) (Hydrocarbons, C6, isoalkanes, <5% n-hexane (CAS-No. 64742-49-0))
Decomposition Temperature	: No data available
Flammability (solid, gas)	: Not applicable
Lower Flammable Limit	: No data available
Upper Flammable Limit	: No data available
Vapor Pressure	: No data available
Relative Vapor Density at 20°C	: No data available
Relative Density	: No data available
Specific Gravity	: No data available
Solubility	: No data available
Partition Coefficient: N-Octanol/Water	: No data available
Viscosity	: No data available
Viscosity, Kinematic	: > 20.5 mm ² /s

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity:

Reacts violently with strong oxidizers. Increased risk of fire or explosion.

10.2. Chemical Stability:

Final Finish

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Highly flammable liquid and vapor. May form flammable or explosive vapor-air mixture.

10.3. Possibility of Hazardous Reactions:

Hazardous polymerization will not occur.

10.4. Conditions to Avoid:

Direct sunlight, extremely high or low temperatures, heat, hot surfaces, sparks, open flames, incompatible materials, and other ignition sources. Protect from sunlight and air.

10.5. Incompatible Materials:

Oxidizers. Avoid aluminum at higher temperatures. Halogenated compounds.

10.6. Hazardous Decomposition Products:

Prolonged exposure to air and light may result in the formation of peroxides.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on Toxicological Effects - Product

Acute Toxicity (Oral): Not classified

Acute Toxicity (Dermal): Not classified

Acute Toxicity (Inhalation): Not classified

LD50 and LC50 Data:

No additional information available

Skin Corrosion/Irritation: Causes skin irritation.

Eye Damage/Irritation: Causes serious eye irritation.

Respiratory or Skin Sensitization: Not classified

Germ Cell Mutagenicity: Not classified

Carcinogenicity: Not classified

Specific Target Organ Toxicity (Repeated Exposure): Cause damage to organs (central nervous system) through prolonged or repeated exposure (inhalation).

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified

Aspiration Hazard: Not classified.

Symptoms/Injuries After Inhalation: Prolonged exposure may cause irritation.

Symptoms/Injuries After Skin Contact: Redness, pain, swelling, itching, burning, dryness, and dermatitis.

Symptoms/Injuries After Eye Contact: Contact causes severe irritation with redness and swelling of the conjunctiva.

Symptoms/Injuries After Ingestion: Ingestion may cause adverse effects.

Chronic Symptoms: Cause damage to organs (central nervous system) through prolonged or repeated exposure (inhalation).

11.2. Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

Acrylic acid (79-10-7)	
LD50 Oral Rat	1337 mg/kg
LD50 Dermal Rabbit	> 2000 mg/kg
LC50 Inhalation Rat	11.1 mg/l (Exposure time: 1 h)
LC50 Inhalation Rat	3.6 mg/l/4h
Solvent naphtha, petroleum, medium aliphatic (64742-88-7)	
LD50 Oral Rat	> 25 ml/kg
LD50 Dermal Rabbit	> 4000 mg/kg
LC50 Inhalation Rat	> 5.28 mg/l/4h
Naphtha, petroleum, hydrotreated light (64742-49-0)	
LD50 Oral Rat	> 5000 mg/kg
LD50 Dermal Rabbit	> 3160 mg/kg
LC50 Inhalation Rat	73680 ppm/4h
Triethanolamine (102-71-6)	
LD50 Oral Rat	6400 mg/kg
LD50 Dermal Rabbit	> 2000 mg/kg
Isopropyl alcohol (67-63-0)	
LD50 Dermal Rabbit	12956 mg/kg (16.4 mL/kg bw)

Final Finish

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

LC50 Inhalation Rat	> 10000 ppm (Exposure time: 6 h)
Octamethylcyclotetrasiloxane (556-67-2)	
LD50 Oral Rat	> 4800 mg/kg (No mortality)
LD50 Dermal Rabbit	> 2.5 ml/kg (No mortality)
LC50 Inhalation Rat	36 mg/l/4h
Stearic acid (57-11-4)	
LD50 Oral Rat	> 5000 mg/kg
LD50 Dermal Rabbit	> 2000 mg/kg
Acrylic acid (79-10-7)	
IARC Group	3
Solvent naphtha, petroleum, medium aliphatic (64742-88-7)	
National Toxicology Program (NTP) Status	Evidence of Carcinogenicity.
Triethanolamine (102-71-6)	
IARC Group	3
Isopropyl alcohol (67-63-0)	
IARC Group	3

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecology - General: Harmful to aquatic life with long lasting effects.

Acrylic acid (79-10-7)	
LC50 Fish 1	222 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [semi-static])
EC50 - Crustacea [1]	95 mg/l (Exposure time: 48 h - Species: Daphnia magna)
ErC50 algae	0.13 mg/l
NOEC Chronic Algae	0.016 mg/l
Solvent naphtha, petroleum, medium aliphatic (64742-88-7)	
LC50 Fish 1	800 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 - Crustacea [1]	> 100 mg/l (Exposure time: 48 h - Species: Daphnia magna)
ErC50 algae	3.7 mg/l
Naphtha, petroleum, hydrotreated light (64742-49-0)	
LC50 Fish 1	8.2 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
Triethanolamine (102-71-6)	
LC50 Fish 1	10600 (10600 – 13000) mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 - Crustacea [1]	1386 mg/l
LC50 Fish 2	1000 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
ErC50 algae	169 mg/l
NOEC Chronic Crustacea	16 mg/l
Isopropyl alcohol (67-63-0)	
LC50 Fish 1	9640 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 - Crustacea [1]	13299 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 Other Aquatic Organisms 1	1000 mg/l (Exposure time: 96 h - Species: Desmodesmus subspicatus)
LC50 Fish 2	11130 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Other Aquatic Organisms 2	1000 mg/l (Exposure time: 72 h - Species: Desmodesmus subspicatus)
Octamethylcyclotetrasiloxane (556-67-2)	
LC50 Fish 1	> 22 µg/l

12.2. Persistence and Degradability

Final Finish	
Persistence and Degradability	May cause long-term adverse effects in the environment.

Final Finish

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

12.3. Bioaccumulative Potential

Final Finish	
Bioaccumulative Potential	Not established.
Acrylic acid (79-10-7)	
Partition coefficient n-octanol/water (Log Pow)	0.46 (at 25 °C)
Solvent naphtha, petroleum, medium aliphatic (64742-88-7)	
BCF Fish 1	(bioaccumulation expected)
Triethanolamine (102-71-6)	
BCF Fish 1	3.9
Partition coefficient n-octanol/water (Log Pow)	-2.53
Isopropyl alcohol (67-63-0)	
Partition coefficient n-octanol/water (Log Pow)	0.05 (at 25 °C)
Octamethylcyclotetrasiloxane (556-67-2)	
BCF Fish 1	(12400 dimensionless)
Partition coefficient n-octanol/water (Log Pow)	6.488 (at 25.1 °C)

12.4. Mobility in Soil

Stearic acid (57-11-4)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	51.05

12.5. Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste Disposal Recommendations: Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

Additional Information: Handle empty containers with care because residual vapors are flammable.

Ecology - Waste Materials: Avoid release to the environment. This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

SECTION 14: TRANSPORT INFORMATION

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

14.1. In Accordance with DOT

Proper Shipping Name : PAINT RELATED MATERIAL
Hazard Class : 3
Identification Number : UN1263
Label Codes : 3
Packing Group : II
Marine Pollutant : Marine pollutant
ERG Number : 128



14.2. In Accordance with IMDG

Proper Shipping Name : PAINT RELATED MATERIAL
Hazard Class : 3
Identification Number : UN1263
Label Codes : 3
Packing Group : II
EmS-No. (Fire) : F-E



Final Finish

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

EmS-No. (Spillage) : S-E

14.3. In Accordance with IATA

Proper Shipping Name : PAINT RELATED MATERIAL

Hazard Class : 3

Identification Number : UN1263

Label Codes : 3

Packing Group : II

ERG Code (IATA) : 3L



14.4. In Accordance with TDG

Not regulated for transport

SECTION 15: REGULATORY INFORMATION

15.1. US Federal Regulations

Final Finish	
SARA Section 311/312 Hazard Classes	Health hazard - Specific target organ toxicity (single or repeated exposure) Health hazard - Skin corrosion or Irritation Physical hazard - Flammable (gases, aerosols, liquids, or solids) Health hazard - Serious eye damage or eye irritation
Acrylic acid (79-10-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active	
Subject to reporting requirements of United States SARA Section 313	
CERCLA RQ	5000 lb
SARA Section 313 - Emission Reporting	1 %
Solvent naphtha, petroleum, medium aliphatic (64742-88-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active	
Naphtha, petroleum, hydrotreated light (64742-49-0)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active	
Triethanolamine (102-71-6)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active	
Poly(oxy-1,2-ethanediyl), .alpha.,.alpha.'-[[[3-(decyloxy)propyl]methyliminio]di-2,1-ethanediyl]bis[.omega.-hydroxy-, branched, chlorides (68478-94-4)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active	
EPA TSCA Regulatory Flag	XU - XU - indicates a substance exempt from reporting under the Chemical Data Reporting Rule, (40 CFR 711).
Isopropyl alcohol (67-63-0)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active	
Subject to reporting requirements of United States SARA Section 313	
SARA Section 313 - Emission Reporting	1 % (only if manufactured by the strong acid process, no supplier notification)
Octamethylcyclotetrasiloxane (556-67-2)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a final TSCA section 4 test rule.
Stearic acid (57-11-4)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active	

15.2. US State Regulations

Acrylic acid (79-10-7)	
U.S. - New Jersey - Right to Know Hazardous Substance List	
U.S. - Pennsylvania - RTK (Right to Know) List	

Final Finish

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

U.S. - Massachusetts - Right To Know List
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

Triethanolamine (102-71-6)

U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Massachusetts - Right To Know List

Isopropyl alcohol (67-63-0)

U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Massachusetts - Right To Know List
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

15.3. Canadian Regulations

Acrylic acid (79-10-7)

Listed on the Canadian DSL (Domestic Substances List)

Solvent naphtha, petroleum, medium aliphatic (64742-88-7)

Listed on the Canadian DSL (Domestic Substances List)

Naphtha, petroleum, hydrotreated light (64742-49-0)

Listed on the Canadian DSL (Domestic Substances List)

Triethanolamine (102-71-6)

Listed on the Canadian DSL (Domestic Substances List)

Poly(oxy-1,2-ethanediyl), .alpha.,.alpha.'-[[[3-(decyloxy)propyl]methyliminio]di-2,1-ethanediyl]bis[.omega.-hydroxy-, branched, chlorides (68478-94-4)

Listed on the Canadian DSL (Domestic Substances List)

Isopropyl alcohol (67-63-0)

Listed on the Canadian DSL (Domestic Substances List)

Octamethylcyclotetrasiloxane (556-67-2)

Listed on the Canadian DSL (Domestic Substances List)

Stearic acid (57-11-4)

Listed on the Canadian DSL (Domestic Substances List)

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Date of Preparation or Latest : 11/10/2022

Revision

Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200 and Canada's Hazardous Products Regulations (HPR) SOR/2015-17.

GHS Full Text Phrases:

H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness

Final Finish

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

H361	Suspected of damaging fertility or the unborn child
H372	Causes damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H401	Toxic to aquatic life
H402	Harmful to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

NA GHS SDS 2015 (Can, US)

Micro-Gloss

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).
Date of Issue: 11/07/2022 Version: 1.0

SECTION 1: IDENTIFICATION

1.1. Product Identifier

Product Form: Mixture

Product Name: Micro-Gloss

1.2. Intended Use of the Product

Polish to remove residual haze on coatings, paint or plastics.

1.3. Name, Address, and Telephone of the Responsible Party

Company

Micro-Surface Finishing Products, Inc.

1217 W 3rd St

PO Box 70

Wilton IA 52778

563.732.3240

www.micro-surface.com

1.4. Emergency Telephone Number

Emergency Number : 563.732.3240

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the Substance or Mixture

GHS-US/CA Classification

Not classified

2.2. Label Elements

GHS-US/CA Labeling

No labeling applicable according to 29 CFR 1910.1200 and the Hazardous Products Regulations (HPR) SOR/2015-17.

2.3. Other Hazards

Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

2.4. Unknown Acute Toxicity (GHS-US/CA)

No additional information available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substance

Not applicable

3.2. Mixture

Name	Synonyms	Product Identifier	% *	GHS Ingredient Classification
Aluminum oxide (Al ₂ O ₃)	Aluminum oxide / .alpha.- Alumina / Alumina / Aluminium oxide / Aluminium oxide (Al ₂ O ₃) / .alpha.- Aluminum oxide / Dialuminium trioxide / Dialuminium trioxide / ALUMINA / Alundum	(CAS-No.) 1344-28-1	10 - 30	Not classified
1,2,3-Propanetriol	Propane-1,2,3-triol / Glycerine / Glycerin / GLYCERIN / 1,2,3- Trihydroxypropane / Glycerol	(CAS-No.) 56-81-5	7 - 13	Not classified

*Percentages are listed in weight by weight percentage (w/w%) for liquid and solid ingredients. Gas ingredients are listed in volume by volume percentage (v/v%).

** The actual concentration of ingredient(s) is withheld as a trade secret in accordance with the Hazardous Products Regulations (HPR) SOR/2015-17 and 29 CFR 1910.1200.

SECTION 4: FIRST AID MEASURES

4.1. Description of First-aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

Micro-Gloss

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Inhalation: When symptoms occur: go into open air and ventilate suspected area. Obtain medical attention if breathing difficulty persists.

Skin Contact: Remove contaminated clothing. Drench affected area with water for at least 5 minutes. Obtain medical attention if irritation develops or persists.

Eye Contact: Rinse cautiously with water for at least 5 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if irritation develops or persists.

Ingestion: Rinse mouth. Do NOT induce vomiting. Obtain medical attention.

4.2. Most Important Symptoms and Effects Both Acute and Delayed

General: Not expected to present a significant hazard under anticipated conditions of normal use.

Inhalation: Prolonged exposure may cause irritation.

Skin Contact: Prolonged exposure may cause skin irritation.

Eye Contact: May cause slight irritation to eyes.

Ingestion: Ingestion may cause adverse effects.

Chronic Symptoms: None expected under normal conditions of use.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Water spray, fog, carbon dioxide (CO₂), alcohol-resistant foam, or dry chemical.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not considered flammable but may burn at high temperatures.

Explosion Hazard: Product is not explosive.

Reactivity: Hazardous reactions will not occur under normal conditions.

5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Carbon oxides (CO, CO₂). Metal oxide fumes. Acrolein. Nitrous oxide.

5.4. Reference to Other Sections

Refer to Section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Avoid prolonged contact with eyes, skin and clothing. Avoid breathing (vapor, mist, spray).

6.1.1. For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protective equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

6.1.2. For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Ventilate area.

6.2. Environmental Precautions

Prevent entry to sewers and public waters.

6.3. Methods and Materials for Containment and Cleaning Up

For Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for Cleaning Up: Clean up spills immediately and dispose of waste safely. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

Micro-Gloss

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Precautions for Safe Handling: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Avoid prolonged contact with eyes, skin and clothing. Avoid breathing vapors, mist, spray.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations.

Storage Conditions: Keep container closed when not in use. Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials.

Incompatible Materials: Strong acids, strong bases, strong oxidizers.

7.3. Specific End Use(s)

Polish to remove residual haze on coatings, paint or plastics.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), OSHA (PEL), or Canadian provincial governments.

1,2,3-Propanetriol (56-81-5)		
USA OSHA	OSHA PEL (TWA) [1]	15 mg/m ³ (mist, total particulate) 5 mg/m ³ (mist, respirable fraction)
Alberta	OEL TWA	10 mg/m ³ (mist)
British Columbia	OEL TWA	10 mg/m ³ (mist, total) 3 mg/m ³ (mist-respirable)
New Brunswick	OEL TWA	10 mg/m ³ (mist)
Nunavut	OEL STEL	20 mg/m ³ (mist)
Nunavut	OEL TWA	10 mg/m ³ (mist)
Northwest Territories	OEL STEL	20 mg/m ³ (mist)
Northwest Territories	OEL TWA	10 mg/m ³ (mist)
Québec	VEMP (OEL TWA)	10 mg/m ³ (mist)
Saskatchewan	OEL STEL	20 mg/m ³ (mist)
Saskatchewan	OEL TWA	10 mg/m ³ (mist)
Yukon	OEL TWA	30 mppcf (mist) 10 mg/m ³ (mist)
Aluminum oxide (Al ₂ O ₃) (1344-28-1)		
USA ACGIH	ACGIH OEL TWA	10 mg/m ³
USA OSHA	OSHA PEL (TWA) [1]	15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction)
Alberta	OEL TWA	10 mg/m ³
New Brunswick	OEL TWA	10 mg/m ³ (particulate matter containing no Asbestos and <1% Crystalline silica)
Nunavut	OEL STEL	20 mg/m ³
Nunavut	OEL TWA	10 mg/m ³
Northwest Territories	OEL STEL	20 mg/m ³
Northwest Territories	OEL TWA	10 mg/m ³
Québec	VEMP (OEL TWA)	10 mg/m ³ (containing no Asbestos and <1% Crystalline silica-total dust)
Saskatchewan	OEL STEL	20 mg/m ³
Saskatchewan	OEL TWA	10 mg/m ³
Yukon	OEL STEL	20 mg/m ³ (Al ₂ O ₃)
Yukon	OEL TWA	30 mppcf (Al ₂ O ₃) 10 mg/m ³ (Al ₂ O ₃)

Micro-Gloss

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

8.2. Exposure Controls

Appropriate Engineering Controls: Suitable eye/body wash equipment should be available in the vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed.

Personal Protective Equipment: Gloves. Protective clothing. Protective goggles.



Materials for Protective Clothing: Chemically resistant materials and fabrics.

Hand Protection: Wear protective gloves.

Eye and Face Protection: Chemical safety goggles.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

Other Information: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties

Physical State	: Liquid
Appearance	: White/ Cream
Odor	: According to product specification
Odor Threshold	: No data available
pH	: No data available
Evaporation Rate	: No data available
Melting Point	: No data available
Freezing Point	: No data available
Boiling Point	: No data available
Flash Point	: No data available
Auto-ignition Temperature	: No data available
Decomposition Temperature	: No data available
Flammability (solid, gas)	: Not applicable
Lower Flammable Limit	: No data available
Upper Flammable Limit	: No data available
Vapor Pressure	: No data available
Relative Vapor Density at 20°C	: No data available
Relative Density	: No data available
Specific Gravity	: No data available
Solubility	: No data available
Partition Coefficient: N-Octanol/Water	: No data available
Viscosity	: No data available

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity:

Hazardous reactions will not occur under normal conditions.

10.2. Chemical Stability:

Stable under recommended handling and storage conditions (see section 7).

10.3. Possibility of Hazardous Reactions:

Hazardous polymerization will not occur.

10.4. Conditions to Avoid:

Direct sunlight, extremely high or low temperatures, and incompatible materials.

10.5. Incompatible Materials:

Strong acids, strong bases, strong oxidizers.

10.6. Hazardous Decomposition Products:

Thermal decomposition may produce: Carbon oxides (CO, CO₂). Acrolein. Nitrogen oxides.

Micro-Gloss

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on Toxicological Effects - Product

Acute Toxicity (Oral): Not classified

Acute Toxicity (Dermal): Not classified

Acute Toxicity (Inhalation): Not classified

LD50 and LC50 Data:

No additional information available

Skin Corrosion/Irritation: Not classified

Eye Damage/Irritation: Not classified

Respiratory or Skin Sensitization: Not classified

Germ Cell Mutagenicity: Not classified

Carcinogenicity: Not classified

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: Prolonged exposure may cause irritation.

Symptoms/Injuries After Skin Contact: Prolonged exposure may cause skin irritation.

Symptoms/Injuries After Eye Contact: May cause slight irritation to eyes.

Symptoms/Injuries After Ingestion: Ingestion may cause adverse effects.

Chronic Symptoms: None expected under normal conditions of use.

Potential Adverse human health effects and symptoms: Based on available data, the classification criteria are not met.

11.2. Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

1,2,3-Propanetriol (56-81-5)	
LD50 Oral Rat	12600 mg/kg
LD50 Dermal Rabbit	> 10 g/kg
Aluminum oxide (Al2O3) (1344-28-1)	
LD50 Oral Rat	> 15900 mg/kg

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecology - General: Not classified.

1,2,3-Propanetriol (56-81-5)	
LC50 Fish 1	54000 (51000 – 57000) mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
Aluminum oxide (Al2O3) (1344-28-1)	
LC50 Fish 1	> 100 mg/l
EC50 - Crustacea [1]	> 100 mg/l
ErC50 algae	> 100 mg/l
NOEC (Acute)	> 50 mg/l

12.2. Persistence and Degradability

Micro-Gloss	
Persistence and Degradability	Not established.

12.3. Bioaccumulative Potential

Micro-Gloss	
Bioaccumulative Potential	Not established.
1,2,3-Propanetriol (56-81-5)	
BCF Fish 1	(no bioaccumulation)
Partition coefficient n-octanol/water (Log Pow)	-1.75 (at 25 °C (at pH 7.4))

12.4. Mobility in Soil

No additional information available

Micro-Gloss

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

12.5. Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste Disposal Recommendations: Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

Ecology - Waste Materials: Avoid release to the environment.

SECTION 14: TRANSPORT INFORMATION

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

14.1. In Accordance with DOT

Not regulated for transport

14.2. In Accordance with IMDG

Not regulated for transport

14.3. In Accordance with IATA

Not regulated for transport

14.4. In Accordance with TDG

Not regulated for transport

SECTION 15: REGULATORY INFORMATION

15.1. US Federal Regulations

1,2,3-Propanetriol (56-81-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

Aluminum oxide (Al₂O₃) (1344-28-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

Subject to reporting requirements of United States SARA Section 313

SARA Section 313 - Emission Reporting

1 % (fibrous forms)

15.2. US State Regulations

1,2,3-Propanetriol (56-81-5)

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

U.S. - Massachusetts - Right To Know List

Aluminum oxide (Al₂O₃) (1344-28-1)

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

U.S. - Massachusetts - Right To Know List

U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

15.3. Canadian Regulations

1,2,3-Propanetriol (56-81-5)

Listed on the Canadian DSL (Domestic Substances List)

Aluminum oxide (Al₂O₃) (1344-28-1)

Listed on the Canadian DSL (Domestic Substances List)

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Date of Preparation or Latest Revision : 11/07/2022

Revision

Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200 and Canada's Hazardous Products Regulations (HPR) SOR/2015-17.

Micro-Gloss

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

NA GHS SDS 2015 (Can, US)

Micro-Gloss #5

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).
Date of Issue: 11/28/2022 Version: 1.0

SECTION 1: IDENTIFICATION

1.1. Product Identifier

Product Form: Mixture

Product Name: Micro-Gloss #5

1.2. Intended Use of the Product

Polish to remove residual haze on coatings, paint or plastics.

1.3. Name, Address, and Telephone of the Responsible Party

Company

Micro-Surface Finishing Products, Inc.

1217 W 3rd St

PO Box 70

Wilton IA 52778

563.732.3240

www.micro-surface.com

1.4. Emergency Telephone Number

Emergency Number : 563.732.3240

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the Substance or Mixture

GHS-US/CA Classification

Not classified

2.2. Label Elements

GHS-US/CA Labeling

No labeling applicable according to 29 CFR 1910.1200 and the Hazardous Products Regulations (HPR) SOR/2015-17.

2.3. Other Hazards

Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

2.4. Unknown Acute Toxicity (GHS-US/CA)

No additional information available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substance

Not applicable

3.2. Mixture

Name	Synonyms	Product Identifier	% *	GHS Ingredient Classification
1,2,3-Propanetriol	Propane-1,2,3-triol / Glycerine / Glycerin / GLYCERIN / 1,2,3-Trihydroxypropane / Glycerol	(CAS-No.) 56-81-5	10 - 30	Not classified
Aluminum oxide (Al ₂ O ₃)	Aluminum oxide / .alpha.-Alumina / Alumina / Aluminium oxide / Aluminium oxide (Al ₂ O ₃) / .alpha.-Aluminum oxide / Dialuminum trioxide / Dialuminium trioxide / ALUMINA / Alundum	(CAS-No.) 1344-28-1	10 - 30	Not classified

*Percentages are listed in weight by weight percentage (w/w%) for liquid and solid ingredients. Gas ingredients are listed in volume by volume percentage (v/v%).

** The actual concentration of ingredient(s) is withheld as a trade secret in accordance with the Hazardous Products Regulations (HPR) SOR/2015-17 and 29 CFR 1910.1200.

SECTION 4: FIRST AID MEASURES

4.1. Description of First-aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

Micro-Gloss #5

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Inhalation: When symptoms occur: go into open air and ventilate suspected area. Obtain medical attention if breathing difficulty persists.

Skin Contact: Remove contaminated clothing. Drench affected area with water for at least 5 minutes. Obtain medical attention if irritation develops or persists.

Eye Contact: Rinse cautiously with water for at least 5 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if irritation develops or persists.

Ingestion: Rinse mouth. Do NOT induce vomiting. Obtain medical attention.

4.2. Most Important Symptoms and Effects Both Acute and Delayed

General: Not expected to present a significant hazard under anticipated conditions of normal use.

Inhalation: Prolonged exposure may cause irritation.

Skin Contact: Prolonged exposure may cause skin irritation.

Eye Contact: May cause slight irritation to eyes.

Ingestion: Ingestion may cause adverse effects.

Chronic Symptoms: None expected under normal conditions of use.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Water spray, fog, carbon dioxide (CO₂), alcohol-resistant foam, or dry chemical.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not considered flammable but may burn at high temperatures.

Explosion Hazard: Product is not explosive.

Reactivity: Hazardous reactions will not occur under normal conditions.

5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Carbon oxides (CO, CO₂). Peroxides. Acrolein. Metal oxides.

5.4. Reference to Other Sections

Refer to Section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Avoid prolonged contact with eyes, skin and clothing. Avoid breathing (vapor, mist, spray).

6.1.1. For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protective equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

6.1.2. For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Ventilate area.

6.2. Environmental Precautions

Prevent entry to sewers and public waters.

6.3. Methods and Materials for Containment and Cleaning Up

For Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for Cleaning Up: Clean up spills immediately and dispose of waste safely. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

Micro-Gloss #5

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Precautions for Safe Handling: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Avoid prolonged contact with eyes, skin and clothing. Avoid breathing vapors, mist, spray.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations.

Storage Conditions: Keep container closed when not in use. Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials.

Incompatible Materials: Strong acids, strong bases, strong oxidizers, alkenes.

7.3. Specific End Use(s)

Polish to remove residual haze on coatings, paint or plastics.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), OSHA (PEL), or Canadian provincial governments.

Aluminum oxide (Al ₂ O ₃) (1344-28-1)		
USA ACGIH	ACGIH OEL TWA	10 mg/m ³
USA OSHA	OSHA PEL (TWA) [1]	15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction)
Alberta	OEL TWA	10 mg/m ³
New Brunswick	OEL TWA	10 mg/m ³ (particulate matter containing no Asbestos and <1% Crystalline silica)
Nunavut	OEL STEL	20 mg/m ³
Nunavut	OEL TWA	10 mg/m ³
Northwest Territories	OEL STEL	20 mg/m ³
Northwest Territories	OEL TWA	10 mg/m ³
Québec	VEMP (OEL TWA)	10 mg/m ³ (containing no Asbestos and <1% Crystalline silica-total dust)
Saskatchewan	OEL STEL	20 mg/m ³
Saskatchewan	OEL TWA	10 mg/m ³
Yukon	OEL STEL	20 mg/m ³ (Al ₂ O ₃)
Yukon	OEL TWA	30 mppcf (Al ₂ O ₃) 10 mg/m ³ (Al ₂ O ₃)
1,2,3-Propanetriol (56-81-5)		
USA OSHA	OSHA PEL (TWA) [1]	15 mg/m ³ (mist, total particulate) 5 mg/m ³ (mist, respirable fraction)
Alberta	OEL TWA	10 mg/m ³ (mist)
British Columbia	OEL TWA	10 mg/m ³ (mist, total) 3 mg/m ³ (mist-respirable)
New Brunswick	OEL TWA	10 mg/m ³ (mist)
Nunavut	OEL STEL	20 mg/m ³ (mist)
Nunavut	OEL TWA	10 mg/m ³ (mist)
Northwest Territories	OEL STEL	20 mg/m ³ (mist)
Northwest Territories	OEL TWA	10 mg/m ³ (mist)
Québec	VEMP (OEL TWA)	10 mg/m ³ (mist)
Saskatchewan	OEL STEL	20 mg/m ³ (mist)
Saskatchewan	OEL TWA	10 mg/m ³ (mist)
Yukon	OEL TWA	30 mppcf (mist) 10 mg/m ³ (mist)

Micro-Gloss #5

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

8.2. Exposure Controls

Appropriate Engineering Controls: Suitable eye/body wash equipment should be available in the vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed.

Personal Protective Equipment: Gloves. Protective clothing. Protective goggles.



Materials for Protective Clothing: Chemically resistant materials and fabrics.

Hand Protection: Wear protective gloves.

Eye and Face Protection: Chemical safety goggles.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

Other Information: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties

Physical State	: Liquid
Appearance	: White/cream
Odor	: According to product specification
Odor Threshold	: No data available
pH	: No data available
Evaporation Rate	: No data available
Melting Point	: No data available
Freezing Point	: No data available
Boiling Point	: No data available
Flash Point	: No data available
Auto-ignition Temperature	: No data available
Decomposition Temperature	: No data available
Flammability (solid, gas)	: Not applicable
Lower Flammable Limit	: No data available
Upper Flammable Limit	: No data available
Vapor Pressure	: No data available
Relative Vapor Density at 20°C	: No data available
Relative Density	: No data available
Specific Gravity	: No data available
Solubility	: Water: Fully miscible
Partition Coefficient: N-Octanol/Water	: No data available
Viscosity	: No data available

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity:

Hazardous reactions will not occur under normal conditions.

10.2. Chemical Stability:

Stable under recommended handling and storage conditions (see section 7).

10.3. Possibility of Hazardous Reactions:

Contains substances that can initiate polymerization in alkenes.

10.4. Conditions to Avoid:

Direct sunlight, extremely high or low temperatures, and incompatible materials.

10.5. Incompatible Materials:

Strong acids, strong bases, strong oxidisers, alkenes.

10.6. Hazardous Decomposition Products:

Can form peroxides by prolonged contact with air and light.

Micro-Gloss #5

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on Toxicological Effects - Product

Acute Toxicity (Oral): Not classified

Acute Toxicity (Dermal): Not classified

Acute Toxicity (Inhalation): Not classified

LD50 and LC50 Data:

No additional information available

Skin Corrosion/Irritation: Not classified

Eye Damage/Irritation: Not classified

Respiratory or Skin Sensitization: Not classified

Germ Cell Mutagenicity: Not classified

Carcinogenicity: Not classified

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: Prolonged exposure may cause irritation.

Symptoms/Injuries After Skin Contact: Prolonged exposure may cause skin irritation.

Symptoms/Injuries After Eye Contact: May cause slight irritation to eyes.

Symptoms/Injuries After Ingestion: Ingestion may cause adverse effects.

Chronic Symptoms: None expected under normal conditions of use.

11.2. Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

Aluminum oxide (Al₂O₃) (1344-28-1)	
LD50 Oral Rat	> 15900 mg/kg
1,2,3-Propanetriol (56-81-5)	
LD50 Oral Rat	12600 mg/kg
LD50 Dermal Rabbit	> 10 g/kg

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

No additional information available

Aluminum oxide (Al₂O₃) (1344-28-1)	
LC50 Fish 1	> 100 mg/l
EC50 - Crustacea [1]	> 100 mg/l
ErC50 algae	> 100 mg/l
NOEC (Acute)	> 50 mg/l
1,2,3-Propanetriol (56-81-5)	
LC50 Fish 1	54000 (51000 – 57000) mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])

12.2. Persistence and Degradability

Micro-Gloss #5	
Persistence and Degradability	Not established.

12.3. Bioaccumulative Potential

Micro-Gloss #5	
Bioaccumulative Potential	Not established.
1,2,3-Propanetriol (56-81-5)	
BCF Fish 1	(no bioaccumulation)
Partition coefficient n-octanol/water (Log Pow)	-1.75 (at 25 °C (at pH 7.4)

12.4. Mobility in Soil

No additional information available

Micro-Gloss #5

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

12.5. Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste Disposal Recommendations: Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

Ecology - Waste Materials: Avoid release to the environment.

SECTION 14: TRANSPORT INFORMATION

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

14.1. In Accordance with DOT

Not regulated for transport

14.2. In Accordance with IMDG

Not regulated for transport

14.3. In Accordance with IATA

Not regulated for transport

14.4. In Accordance with TDG

Not regulated for transport

SECTION 15: REGULATORY INFORMATION

15.1. US Federal Regulations

Aluminum oxide (Al₂O₃) (1344-28-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active
Subject to reporting requirements of United States SARA Section 313

SARA Section 313 - Emission Reporting

1 % (fibrous forms)

1,2,3-Propanetriol (56-81-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

15.2. US State Regulations

Aluminum oxide (Al₂O₃) (1344-28-1)

U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Massachusetts - Right To Know List
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

1,2,3-Propanetriol (56-81-5)

U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Massachusetts - Right To Know List

15.3. Canadian Regulations

Aluminum oxide (Al₂O₃) (1344-28-1)

Listed on the Canadian DSL (Domestic Substances List)

1,2,3-Propanetriol (56-81-5)

Listed on the Canadian DSL (Domestic Substances List)

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Date of Preparation or Latest : 11/28/2022

Revision

Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200 and Canada's Hazardous Products Regulations (HPR) SOR/2015-17.

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

Micro-Gloss #5

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

NA GHS SDS 2015 (Can, US)